

HC/49US (AT49) SMD LOW PROFILE CRYSTAL

ABLS



RoHS
Compliant



11.5 x 4.7 x 4.2 mm

FEATURES:

- Suitable for RoHS reflow
- Available for tight stability & extended temperature range

APPLICATIONS:

- Computers, Modems, Microprocessors
- Automotive and Industrial
- Wireless Applications

OPTIONS AND PART IDENTIFICATION (left blank if standard)

ABLS – xxxxxMHZ-B2-T	10pF 20/50ppm -20/+70°C	1K/Reel
ABLS – xxxxxMHZ-B4-T	18pF 30/50ppm -20/+70°C	1K/Reel
ABLS – xxxxxMHZ-B4Y-T	18pF 30/30ppm -20/+70C	1K/Reel
ABLS – xxxxxMHZ-K4-T	18pF 30/50ppm -40/+125°C	1K/Reel
ABLS – xxxxxMHZ-L4Q-T	18pF 30/100ppm -55/+125°C	1K/Reel
ABLS – xxxxxMHZ-D4Y-T	18pF 30/30ppm -40/+85°C	1K/Reel
ABLS – xxxxxMHZ-10-J4Y-T	10pF 30/30ppm -40/+105°C	1K/Reel


STANDARD SPECIFICATIONS:

PARAMETERS	
ABRACON P/N	ABLS Series
Frequency	3.579545 MHz to 75 MHz
Operation Mode	AT cut (Fundamental or 3rd OT) or BT cut (See options) 3.579545MHz - 24.0MHz (Fundamental: Standard) 24.01MHz - 75.00MHz (3rd- Overtone: Standard) 24.01MHz - 50.00MHz (Fund. AT or BT: See options)
Operating Temperature	0°C to + 70°C (see options)
Storage Temperature	- 55°C to + 125° C
Frequency Tolerance at +25°C	± 50 ppm max. (see options)
Frequency Stability over the Operating Temp. (Ref to +25°C)	± 50 ppm max. (see options)
Equivalent Series Resistance	See Table 1
Shunt Capacitance C ₀	7pF max .
Load Capacitance C _L	18pF (see options)
Drive Level	1 mW max., 100 μW typical
Aging at 25°C (first year)	± 5ppm max .
Insulation Resistance	500 MΩ min at 100Vdc ± 15V
Spurious Responses	-3dB max.
Drive level dependency (DLD)	from 1 μW to 500 μW (minimum 7 points tested)

TABLE 1: STANDARD ESR

FREQUENCY (MHz)	ESR (Ω) MAX
3.579 - 4.999 (Fund.)	180
5.000 - 5.999 (Fund.)	120
6.000 - 7.999 (Fund.)	100
8.000 - 8.999 (Fund.)	80
9.000 - 9.999 (Fund.)	60
10.000 - 15.999 (Fund.)	50
16.000 - 50.000 (Fund.)	40
24.01 - 31.999 (3rd O/T)	100
32.000 - 75.00 (3rd O/T)	80

ABRACON IS
ISO9001:2008
CERTIFIED



ABRACON
CORPORATION

Visit www.abracon.com for Terms & Conditions of Sale

30332 Esperanza, Rancho Santa Margarita, California 92688
tel 949-546-8000 | fax 949-546-8001 | www.abracon.com

Revised: 04.07.11