

ES2211 Surge & Safety X1Y2, SMD ES2215

Kapazitätswerte & Max Spannung							
Wert (pF)	Code	Volt max	Dielectric	Wert (pF)	Code	Volt max	Dielectric
ES2211 Serie				ES2211 Serie			
5.0	5R0	250Vac/5KV	NPO (COG)	470	471	250Vac/3KV	NPO (COG)
6.8	6R8	I	NPO (COG)	560	561	I	NPO (COG)
8.2	8R0	I	NPO (COG)	680	681	▼	NPO (COG)
10	100	I	NPO (COG)				
12	120	I	NPO (COG)				
15	150	I	NPO (COG)				
18	180	I	NPO (COG)				
22	220	I	NPO (COG)				
27	270	I	NPO (COG)	ES2215 Serie			
33	330	I	NPO (COG)	1000 (1.0nF)	102	250Vac/5KV	NPO (COG)
47	470	I	NPO (COG)				
56	560	I	NPO (COG)				
68	680	I	NPO (COG)				
100	101	I	NPO (COG)		250VAC Approved Certified to IEC60384-14		
120	121	I	NPO (COG)				
150	151	I	NPO (COG)				
180	181	I	NPO (COG)				
220	221	I	NPO (COG)	EN60950, EN132400, EN61004-5			
270	271	I	NPO (COG)				
330	331	I	NPO (COG)				
390	391	▼	NPO (COG)				

Irrtümer, Änderungen vorbehalten

2215 Bauforn	N Dielectric	102 Kapazität	K Toleranz	502 Spannung	N Kontaktierung	(X) T Gurtung	M
ES2211 ES2215	N = NPO (COG)	100 = 10pF 101 = 100pF 471 = 470pF 102 = 1000pF	J = 5% K = 5%	502 = 3000V	N = Ni RoHS	T = gegurtet X = Dicke	Marking

Aktuelle Preise auf Anfrage / Current Prices on Request