

Safety X1/Y2 Keramik Caps



Selection Chart: ES1808, ES2211, ES2215 COG Class 1 (+/- 30ppm/°C) X1/Y2 TÜV
 Capacitance Range RoHS COMPLIANT

Cap pF	Size	Tol	250VAC/ 5000V	250VAC/5000V	250VAC/5000V
8R2	1808+	5	ES1808N8R2B502NTM	ES2211N8R2D502NTM	
10	1808+	5	ES1808N100J502NTM	ES2211N100J502NTM	
12	1808+	5	ES1808N120J502NTM	ES2211N120J502NTM	
15	1808+	5	ES1808N150J502NTM	ES2211N150J502NTM	
18	1808+	5	ES1808N180J502NTM	ES2211N180J502NTM	
22	1808+	5	ES1808N220J502NTM	ES2211N220J502NTM	
27	1808+	5	ES1808N270J502NTM	ES2211N270J502NTM	
33	1808+	5	ES1808N330J502NTM	ES2211N330J502NTM	
39	1808+	5	ES1808N390J502NTM	ES2211N390J502NTM	
47	1808+	5	ES1808N470J502NTM	ES2211N470J502NTM	
56	1808+	5	ES1808N560J502NTM	ES2211N560J502NTM	
68	1808+	5	ES1808N680J502NTM	ES2211N680J502NTM	
82	1808+	5	ES1808N820J502NTM	ES2211N820J502NTM	
100	1808+	10	ES1808N101K502NTM	ES2211N101K502NTM	
150	1808+	10	ES1808N151K502NTM	ES2211N151K502NTM	
220	1808+	10	ES1808N221K502NTM	ES2211N221K502NTM	
330	2211	10		ES2211N331K502NTM	
470	2211	10		ES2211N471K502NTM	
560	2211	10		ES2211N561K502NTM	
680	2211	10		ES2211N681K502NTM	
1000	2215	10			ES2215N102K502NTM

Selection Chart: ES1808, X7R Class 2 (+/- 15%) X1/Y2 TÜV RoHS COMPLIANT
 Capacitance Range

Cap pF	Size	Tol	250VAC / 5000V		
150	1808	10	ES1808B151K502NTM		
180	1808	10	ES1808B181K502NTM		
220	1808	10	ES1808B221K502NTM		
270	1808	10	ES1808B271K502NTM		
330	1808	10	ES1808B331K502NTM		
390	1808	10	ES1808B391K502NTM		
470	1808	10	ES1808B471K502NTM		
560	1808	10	ES1808B561K502NTM		
680	1808	10	ES1808B681K502NTM		
820	1808	10	ES1808B821K502NTM		
1000	1808	10	ES1808B102K502NTXM		