

Safety X2/Y3 Keramik Caps



Selection Chart: **LS1808, LS1812 COG Class 1** (+/- 30ppm/°C) **X2/Y3 TÜV/UL**
 Capacitance Range **RoHS COMPLIANT**

Cap pF	Size	Tol	250VAC/ 3000V	250VAC/3000V	250VAC/3000V
8R2	1808	5	LS1808N8R2B302NTM		
10	1808	5	LS1808N100J302NTM		
12	1808	5	LS1808N120J302NTM		
15	1808	5	LS1808N150J302NTM		
18	1808	5	LS1808N180J302NTM		
22	1808	5	LS1808N220J302NTM		
27	1808	5	LS1808N270J302NTM		
33	1808	5	LS1808N330J302NTM		
39	1808	5	LS1808N390J302NTM		
47	1808	5	LS1808N470J302NTM		
56	1808	5	LS1808N560J302NTM		
68	1808	5	LS1808N680J302NTM		
82	1808	5	LS1808N820J302NTM		
100	1808	10	LS1808N101K302NTM		
120	1808	10	LS1808N121K302NTM		
150	1808	10	LS1808N151K302NTM		
220	1808	10	LS1808N221K302NTM		
330	1808	10	LS1808N331K302NTM		
470	1808	10	LS1808N471K302NTM		
680	1808	10	LS1808N681K302NTM		
820	1808	10	LS1808N821K302NTXM		
1000	1808+	10	LS1808N102K302NXTM	LS1812N102K302NTM	
1500	1812	10		LS1812N152K302NTM	
1800	1812	10		LS1812N182K302NXTM	
2200	1812	10		LS1812N222K302NXTM	LS1812N222K302NX100TM

Selection Chart: **LS1808, X7R Class 2** (+/- 15%) **X2/Y3 TÜV/UL**
 Capacitance Range **RoHS COMPLIANT**

Cap pF	Size	Tol	250VAC / 3000V		
150	1808	10	LS1808B151K302NTM		
180	1808	10	LS1808B181K302NTM		
220	1808	10	LS1808B221K302NTM		
270	1808	10	LS1808B271K302NTM		
330	1808	10	LS1808B331K302NTM		
390	1808	10	LS1808B391K302NTM		
470	1808	10	LS1808B471K302NTM		
560	1808	10	LS1808B561K302NTM		
680	1808	10	LS1808B681K302NTM		
820	1808	10	LS1808B821K302NTM		
1000	1808	10	LS1808B102K302NTM		
1200	1808	10	LS1808B122K302NTM		
1500	1808	10	LS1808B152K302NTM		